

# SPM-200R/250R/300R ROTARY PREMADE POUCH PACKING MACHINE

Speed up to 60 bags per minute !

## FEATURES

- Automatic 8 stations for pre-made bags packaging
- Automatic Pick & Place bag infeed system
- Siemens PLC control with touch screen operation
- Multi-Language HMI
- Date Coding
- 304 stainless steel frame
- Storage for 100 product recipes
- Production parameter memory including gripper size, machine speed, sealing temperature, and filling volume
- Pouch presence detection – no filling, no sealing
- Bag deflation with wire guide or push bars
- The two-step sealing process guarantees clean sealing
- Cooling station for liquid products

## OPTIONS

- Various filling systems for powder, granule, liquid, snacks, herbal, or other customized products
- Zipper opening & Sealing device
- Date coding
- Metal detectors
- Checkweigher
- Bag deflators
- Dust suction nozzles and dust collector
- Material infeed conveyor
- Collating discharge conveyor
- Ethernet connectivity
- Automatic deoxidizer & spoon feeding station



## SPECIFICATIONS

Model	SPM-200R	SPM-250R	SPM-300R
Numbers of Stations	8		
Packing Speed	25-60 bags/min	25-50 bags/min	20-35 bags/min
Packaging Size	Length: 100-350 mm (1.6-5.5") Width: 90-200 mm (1.2-3.2")	Length: 120-400 mm (4.7-17.7") Width: 120-250 mm (2.0-6.3")	Length: 150-500 mm (4.7-19.7") Width: 150-320 mm (2.0-7.9")
Air Consumption	0.4m <sup>3</sup> /min	0.5m <sup>3</sup> /min	0.6 m <sup>3</sup> /min
Power	2.3KW	3.5KW	4.5KW
Voltage	380V 50/60Hz		
Machine Weight	1300KG (1100 lbs)	1400KG (2116 lbs)	1500KG (2257 lbs)
Film Material	Laminated film, laminated paper film, aluminum foil film		
Bag Optional Features	Hanging hole, euro slot, carry handle, degassing valve, tear notch, zipper, spout		

